

SERIES 65

HARDENED STEEL CAM LOCK HOUSING OUR FLAGSHIP, PATENTED AXIAL PIN TUMBLER MECHANISM.



OVERVIEW

Anti-manipulation, key control, high security.

Camlock's flagship AXIAL pin tumbler mechanism utilised a series of single, flag-shaped pins that cannot be bumped into place, alongside a set of anti-manipulation features, an anti-drill pillar, and an additional anti-drill roller to prevent drive-through. Available in 18mm, 25 and 30mm body lengths. A wide range of compatible cams are available to order in addition to this cylinder.

Product features

- o Hardened steel anti-drill pillar to deflect drilling
- ${\bf o}\,$ Additional anti-drill roller to protect the cam and latch
- o No shear line = bump resistant
- o Ideal for superior key control
- o Can cross suite with Series 63

TECHNICAL DATA


Number of key differs	over 5.7 million
Protective features	Anti-drill pillar, anti-drill roller
Mechanism	Axial Pin Tumbler
Body material	Hardened steel
Patent protection	Yes
Key registration	Yes
Cross suiting (within the Axial family)	Yes
Master keying	No
Key suite options	Keyed alike and keyed to differ
Body length	18mm, 25mm, 30mm
Fixing hole dimensions	Standard 19mm x 16mm 'double D' punch
Lock fixing	Body nut (supplied)
Key operations	Three options available




TECHNICAL DRAWINGS

ADDITIONAL PRODUCT IMAGES

Series 65 18mm











Series 65 25mm







KEY OPERATIONS

Additional free positions (key movements: 3,4,5,6 and 9) available to special order, subject to quantity.



Key movement: 1

Key starting position: 12 o'clock Key rotation: 90° Key ending position: 3 o'clock Key when unlocked: Trapped



Key movement: 2

Key starting position: 12 o'clock Key rotation: 90° Key ending position: 9 o'clock Key when unlocked: Trapped



Key movement: 3 (subject to MOQ)

Key starting position: 12 o'clock Key rotation: 90° Key ending position: 3 o'clock Key when unlocked: Free

Series 65 30mm

